Nov 05, 2026

Product data sheet

HTND3H230E

Characteristics

Voltage stabilizer, HTND, 3 kVA, terminal connect, 230 V output, digital meter



Main

Range of product	HTND
Product or component type	Voltage stabilizer
Technology type	Servo motor
Rated power in VA	3 kVA
Provided equipment	User manual
Output voltage	230 V

Complementary

Response time	1 s
Efficiency	92 %
Input voltage limits	140...250 V
Protection type	Overvoltage Short-circuit
Network frequency	50/60 Hz
Mounting mode	Desktop installation

Environment

Ambient air temperature for operation	-5…40 °C
Relative humidity	0…90 %
Humidity storage	0…90 %
Operating altitude	0...2000 m
Storage altitude	0…2000 m
Standards	EN 61000-6-2 EN 61000-6-4 EN 61558-1
Product certifications	CE

Offer Sustainability

Sustainable packaging	No

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.