Nov 10, 2026

# Product data sheet

# HWDCV1S2

## Characteristics

**Switch, Curvo Series, 10 AX, 250 V AC, 1 gang, 2-way, white**



## Main

| | |
|---|---|
| Range of product | Curvo |
| Product or component type | Switch |
| Device presentation | Complete mechanism |
| Device mounting | Flush |
| Number of gangs | 1 gang |
| Device application | Light control |
| Colour tint | White |

## Complementary

| | |
|---|---|
| Switch function | 2-way |
| Rated current | 10 AX |
| [Ue] rated operational voltage | 250 V |
| Network type | AC |
| Network frequency | 50 Hz |
| Number of modules | 1 module |
| Actuator | Rocker |
| Material | PC (polycarbonate) |
| Contacts material | Copper |
| Connections - terminals | Screw terminals |
| Type of installation | Indoor |
| Width | 85.7 mm |
| Height | 85.7 mm |

## Environment

| | |
|---|---|
| Ambient air temperature for operation | -5…40 °C |
| Relative humidity | 0…95 % |
| IP degree of protection | IPx0 |
| Standards | IEC 60669-1 |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

## Contractual warranty

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.